

Appl. No. 10/782,201  
Amdt. dated January 25, 2005  
Reply to Office Action of December 15, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Please cancel claims 43-48 and 52-54 without prejudice.

Claims 1-54 (canceled)

55. (previously presented): A direct memory access (DMA) controller disposed within a processing system, the DMA controller connected to a system data bus (SDB), the system data bus carrying data to a processor connected to the system data bus, the DMA controller further connected to a core memory within the processing system, the DMA controller operable to read from or write to the core memory, the DMA controller operable to read from or write to the SDB, the DMA controller comprising:

a first transfer controller running in its own thread of execution independent of another processor disposed with the processing system to carry out data transfers between the system data bus and the core memory, the first transfer controller having a data queue, a first execution unit for transferring data between the core memory and the data queue, and a second execution unit for transferring data between the SDB and the data queue, the second execution unit having at least active and deactivate states;

a first outbound transfer instruction, when executed by the first execution unit, causing the first execution unit to transfer data from the core memory to the data queue; and

Appl. No. 10/782,201  
Amdt. dated January 25, 2005  
Reply to Office Action of December 15, 2004

a second outbound transfer instruction, when executed by the second execution unit in the active state, causing the second execution unit to transfer data from the data queue to the SDB.

56. (previously presented): The DMA controller of claim 55 further comprising:

a first inbound transfer instruction, when executed by the second execution unit in the active state, causing the second execution unit to transfer data from the SDB to the data queue;  
and

a second inbound transfer instruction, when executed by the first execution unit, causing the first execution unit to transfer data from the data queue to the core memory.

57. (previously presented): The DMA controller of claim 56 wherein the DMA controller transfers data to core memory from a second DMA controller connected to the SDB, the second execution unit executing the first inbound transfer instruction, the first execution unit executing the second inbound transfer instruction;

58. (previously presented): The DMA controller of claim 56

wherein the DMA controller transfers data to core memory from a second DMA controller connected to the SDB;

wherein the first transfer controller further comprises a slave address, the second DMA controller writes the data to the slave address bypassing the second execution unit in the deactive state and queuing the data directly to the data queue; and

wherein the first execution unit executes the second inbound transfer instruction to transfer the data from the data queue to the core memory.

59. (previously presented): The DMA controller of claim 55

Appl. No. 10/782,201  
Amdt. dated January 25, 2005  
Reply to Office Action of December 15, 2004

wherein the DMA controller transfers data to a second DMA controller connected to the SDB;

wherein the first transfer controller further comprises a slave address;

wherein the second execution unit is deactivated; and

wherein the first execution unit executes the first outbound transfer instruction to transfer from the core memory to the data queue, the second DMA controller retrieves the data from the data queue by reading the slave address;

60. (previously presented): The DMA controller of claim 56 further comprising:

a second transfer controller connected to the core memory over an independent data path and the SDB, the second transfer controller controlling concurrent data transfer in a first direction between the core memory and the SDB, the first transfer controller controlling data transfer in a second direction between the core memory and the SDB, the first direction is opposite to the second direction.

61. (previously presented): A method for transferring data by a DMA controller disposed within a processing system having core memory and a system data bus (SDB), the DMA controller having a transfer controller, the transfer controller having first execution unit, a second execution unit, and a data queue, the method comprising:

operating the transfer controller in its own thread of execution independent of another processor disposed within the processing system;

executing a first outbound transfer instruction by the first execution unit to transfer data from the core memory to the data queue;

Appl. No. 10/782,201  
Amdt. dated January 25, 2005  
Reply to Office Action of December 15, 2004

activating the second execution unit; and  
executing a second outbound transfer instruction by the second execution unit to transfer data from the data queue to the SDB.

62. (previously presented): The method of claim 61 wherein the method transfers data to core memory from a second DMA controller connected to the SDB, the method further comprising:

executing a first inbound transfer instruction by a second execution unit to transfer data from the SDB to the data queue; and

executing a second inbound transfer instruction by a first execution unit to transfer data from the data queue to the core memory.

63. (previously presented): The method of claim 61 wherein the method transfers data to core memory from a second DMA controller connected to the SDB, the method further comprising:

deactivating the second execution unit;

writing data by the second DMA controller to a slave address in the transfer controller to queue the data directly to the data queue; and

executing the second inbound transfer instruction to transfer the data from the data queue to the core memory.

64. (previously presented): The DMA controller of claim 61 wherein the method transfers data to a second DMA controller through the SDB, the method comprising:

deactivating the second execution unit;

Appl. No. 10/782,201  
Amdt. dated January 25, 2005  
Reply to Office Action of December 15, 2004

executing the first outbound transfer instruction to transfer from the core memory to the data queue; and

reading a slave address to retrieve the data from the data queue over the SDB.